

TYPE	MANUFACTURER	SERIES	INSTALLATION	LENGHT	LUMEN OUTPUT	OPTIC	REFLECTOR	VOLTAGE	WATTS	TEMPERATURE (°K)	DRIVER TYPE	NUMBER OF DRIVER	OPTION	
D1A	EATON	SWLED	WALL MOUNTED / SUSPENDED CEILING	4'-0"	4800	FULL FROST LENS	N/A	120V	43.3	3500K	0-10V	1	NOTE: PROVIDE A TOTAL OF 4 REMOTES. OPTIONS: SVPD2 (MOTION SENSOR), ACCESSORIES: ISHH-01	
D1B	EATON	SWLED	WALL MOUNTED / SUSPENDED CEILING	4'-0"	4800	FULL FROST LENS	N/A	120V	43.3	3500K	0-10V	1		
D1C	EATON	SWLED	WALL MOUNTED / SUSPENDED CEILING	2'-0"	1600	FULL FROST LENS	N/A	120V	18.9	3500K	0-10V	1		
D1D	EATON	SNLED	WALL MOUNTED / SUSPENDED CEILING	2'-0"	1600	FULL FROST LENS	N/A	120V	15	3500K	0-10V	1		NOTE: PROVIDE A WIREGUARD
D1E	EATON	SNLED	WALL MOUNTED / SUSPENDED CEILING	4'-0"	3600	FULL FROST LENS	N/A	120V	30	3500K	0-10V	1		NOTE: PROVIDE A WIREGUARD
D2A	EATON	24SR	SUSPENDED CEILING	4'-0"	2900	STD	CURVED	120V	22.7	3500K	0-10V	1	NOTE: PROVIDE A SURFACE MOUNT KIT AND STEMS TO SUSPEND FIXTURE	
D2B	EATON	24SR	GYPSUM CEILING	4'-0"	2900	STD	CURVED	120V	22.7	3500K	0-10V	1		
D2C	EATON	24SR	SUSPENDED CEILING	4'-0"	3900	STD	CURVED	120V	27.2	3500K	0-10V (1-100%)	1		
D2D	EATON	24SR	SUSPENDED CEILING	4'-0"	3900	STD	CURVED	120V	27.2	3500K	0-10V	1		
D3A	EATON	22SR	SUSPENDED CEILING	2'-0"	2000	STD	CURVED	120V	15.4	3500K	0-10V (1-100%)	1		
D3B	EATON	22SR	SUSPENDED CEILING	2'-0"	2900	STD	CURVED	120V	23.4	3500K	0-10V (1-100%)	1	NOTE: PROVIDE A SURFACE MOUNT KIT AND STEMS TO SUSPEND FIXTURE	
D3C	EATON	22SR	SUSPENDED CEILING	2'-0"	2900	STD	CURVED	120V	23.4	3500K	0-10V	1		
D3D	EATON	22SR	SUSPENDED CEILING	2'-0"	2000	STD	CURVED	120V	15.4	3500K	0-10V	1		
D4A	EATON	14SR	SUSPENDED CEILING	4'-0"	2000	STD	CURVED	120V	16.4	3500K	0-10V	1		
D4B	EATON	14SR	GYPSUM CEILING	4'-0"	2000	STD	CURVED	120V	16.4	3500K	0-10V	1		
D4C	EATON	14SR	SUSPENDED CEILING	4'-0"	2000	STD	CURVED	120V	16.4	3500K	0-10V	1	NOTE: PROVIDE A SURFACE MOUNT KIT AND STEMS TO SUSPEND FIXTURE	
D4D	EATON	14SR	SUSPENDED CEILING	4'-0"	2500	STD	CURVED	120V	20.9	3500K	0-10V	1		
D4E	EATON	14SR	GYPSUM CEILING	4'-0"	2500	STD	CURVED	120V	20.9	3500K	0-10V	1		
D5A	EATON	LD6B	SUSPENDED CEILING	6" Ø	2000	N/A	N/A	120V	21.2	3500K	0-10V (1-100%)	1		NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SEMI-SPECULAR CLEAR FINISH
D5B	EATON	LD6B	SUSPENDED CEILING	6" Ø	1000	N/A	N/A	120V	11	3500K	0-10V (1-100%)	1		NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SEMI-SPECULAR CLEAR FINISH
D5C	EATON	LD6B	GYPSUM CEILING	6" Ø	2000	N/A	N/A	120V	21.2	3500K	0-10V (1-100%)	1	NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SEMI-SPECULAR CLEAR FINISH	
D6A	EATON	LD4B	SUSPENDED CEILING	4" Ø	1000	N/A	N/A	120V	11	3500K	0-10V (1-100%)	1	NOTE: MEDIUM DISTRIBUTION, WHITE FLANGE, SPECULAR BLACK FINISH	
D6B	EATON	LD4B	SUSPENDED CEILING	4" Ø	1000	N/A	N/A	120V	11	3500K	0-10V (1-100%)	1	NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SPECULAR BLACK FINISH	
D6C	EATON	LD4B	SUSPENDED CEILING	4" Ø	1500	N/A	N/A	120V	15.5	3500K	0-10V (1-100%)	1	NOTE: MEDIUM DISTRIBUTION, WHITE FLANGE, SPECULAR BLACK FINISH	
D6D	EATON	LD4B	SUSPENDED CEILING	4" Ø	1500	N/A	N/A	120V	15.5	3500K	0-10V (1-100%)	1	NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SEMI-SPECULAR CLEAR FINISH	
D6E	EATON	LD4B	SUSPENDED CEILING	4" Ø	1000	N/A	N/A	120V	11	3500K	0-10V (1-100%)	1	NOTE: WIDE DISTRIBUTION, WHITE FLANGE, SEMI-SPECULAR CLEAR FINISH AND IP68 GASKET KIT	
D7	EATON	HALO RL56	SUSPENDED CEILING	4" Ø	690	N/A	N/A	120V	12	3500K	N/A	1	NOTE: WHITE TRIM. OPTIONS: 90 CRI	
D8A	EATON	VHB	CEILING	4'-0"	18 000	N/A	N/A	120V	160	4000K	0-10V	1	OPTIONS: PAINTED AFTER FABRICATION / WIREGUARD	
D8B	EATON	VHB	CEILING	4'-0"	12 000	N/A	N/A	120V	100	4000K	0-10V	1	OPTIONS: PAINTED AFTER FABRICATION / WIREGUARD	
D9	EATON	VAPORTITE			4 000	FROSTED LENS	N/A	120V	38	4000K	0-10V	1		
D10	EATON	BCLED	WALL MOUNTED	4'-0"	2800	FROSTED LENS	N/A	120V	29	3500K	0-10V	1	SF1(VANDAL RESISTANT SCREWS, ALHA)(ALUMINIUM PAINTED, NOTE: COLOR TO BE CHOOSE BY ARCHITECT.	
D11	EATON	HVSL	WALL MOUNTED	4'-0"	4300	OPAL								

[illegible]

Architect

JLR **J.L.Richards**
ENGINEERS · ARCHITECTS · PLANNERS
www.jlrichards.ca

Seal



2018-06-01

Title

ELECTRICAL
LEGEND

Drawing n°	Revision
E-002	0